

PRODUCT SPECIFICATION SHEET

ARS26 Wheel Straightening Machine

CNC alloy wheel lathe for professional diamond-cut refurbishment — compact side-entry design, 10'–26' wheel range.

10'–26'	1.5 kW	0–300 r/min	350 kg
WHEEL RANGE	MOTOR POWER	SPINDLE SPEED	WEIGHT

Technical Specifications

Model	ARS26
Dimension (L×W×H)	1330 × 810 × 1410 mm
Weight	350 kg
Tool Post	4
Wheel Repair Range	10'–26' inch
Motor Power	1.5 kW
Speed Range of Spindle	0–300 r/min
Power Supply	220V single-phase or 380V 3-phase (specify on order)
Warranty	12 months

ARS26 vs ARS26H — Key Difference

Feature	ARS26	ARS26H
Tool approach	Side entry	Overhead (above wheel centre)
Standard flat-face wheels	✓	✓
Deep-dish / concave rims	Limited by geometry	✓ Full face access
Wheel repair range	10'–26'	10'–26'
Motor power	1.5 kW	1.5 kW

Best for Mainstream passenger vehicles Premium / performance vehicles
Custom voltage configuration available at factory. Contact us to confirm lead time and freight to your destination.

Tel / WhatsApp: +86 139 0672 0286 Email: info@inovatecmachinery.com 399# Shushan Road, Huzhou, Zhejiang, China	Request a quote or ask about a matched wheel line Reply within 24 hours with pricing and recommendations.
--	---